





	Bloccaggio	Codice					Certificazione	Peso
<b>Moschettoni in alluminio</b>								
<b>WILLIAM</b>	SCREW-LOCK	M36 SL / SLN	25 mm	25 kN	7 kN	7 kN	CE EN 362	90 g
	TRIACT-LOCK	M36 TL / TLN	24 mm					
	BALL-LOCK	M36 BL	24 mm					
<b>Am'D</b>	SCREW-LOCK	M34 SL	21 mm	28 kN	7 kN	8 kN	CE EN 362	75 g
	TRIACT-LOCK	M34 TL	21 mm					
	BALL-LOCK	M34 BL	22 mm					
<b>OK</b>	SCREW-LOCK	M33 SL / SLN	19 mm	24 kN	10 kN	7 kN	CE EN 362	75 g
	TRIACT-LOCK	M33 TL / TLN	19 mm		8 kN			
<b>Moschettoni in acciaio</b>								
<b>OXAN</b>	SCREW-LOCK	M72 SL / SLN	21 mm	27 kN	16 kN	7 kN	CE EN 362, NFPA 1983, Light Use	195 g
	TRIACT-LOCK (norme europee)	M72 TL	21 mm					215 g
	TRIACT-LOCK (norme europee e del Nord America)	M72 TLA / TLN	19 mm				235 g	
<b>VULCAN</b>	SCREW-LOCK	M73 SL / SLN	31 mm	40 kN	16 kN	11 kN	CE EN 362, NFPA 1983, General Use	265 g
	TRIACT-LOCK (norme europee)	M73 TL	30 mm					285 g
	TRIACT-LOCK (norme europee e del Nord America)	M73 TLA / TLN	29 mm				305 g	
<b>Connettori di grandi dimensioni</b>								
<b>MGO</b>	Automatico	MGO60	60 mm	25 kN	-	-	CE EN 362	455 g
		MGO110	110 mm	23 kN	15 kN	7 kN	CE EN 362	940 g
<b>Moschettoni speciali in alluminio</b>								
<b>OMNI</b>	SCREW-LOCK	M37 SL / SLN	22 mm	20 kN	15 kN	7 kN	CE EN 362	85 g
	TRIACT-LOCK	M37 TL / TLN	22 mm					90 g
<b>FREINO</b>	TWIST-LOCK	M42	15 mm	25 kN	10 kN	9 kN	CE EN 362	85 g
<b>SPIRIT</b>	-	M15 A	20 mm	23 kN	10 kN	9,5 kN	CE EN 12275 tipo B	50 g
<b>Maglie rapide</b>								
<b>DELTA</b>	Maglia rapida	P11	12 mm	25 kN	10 kN	-	CE EN 362 tipo Q	150 g
		P11-8 / P11-8B	10 mm	25 kN	10 kN	-	CE EN 362 tipo Q	85 / 95 g
<b>GO</b>	Maglia rapida	P15	16 mm	25 kN	10 kN	-	CE EN 362 tipo Q	60 g
<b>DEMI ROND</b>	Maglia rapida	P18	10 mm	25 kN	10 kN	-	CE EN 362 tipo Q	55 g