

• **In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person.** Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • **PPE inspection should be conducted with the manufacturer's Instructions for Use.**
 Download the instructions at [PETZL.COM](https://www.petzl.com).

PROGRESS ADJUST

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

				N/A
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

				N/A
---	---	---	---	-----

2. Preliminary observations

Verify the presence and legibility of the serial number and the CE mark.
 Verify that the product lifetime has not been exceeded.
 Compare with a new device to verify there are no modifications or missing parts.

3. Checking the condition of the rope

- Remove the connectors from the individual strands. Remove the protective sleeve from the lanyard side, and the rope clamp, in order to check the hidden areas.
- Look for wear and damage on the sheath due to use (cuts, fuzziness, chemical residues...)
- Do a tactile inspection of the core for the full length of the rope (hard spots, swelling, soft or crushed areas...)
- Check the condition of the rope at the harness attachment holes and at the ends of the lanyard.
- Check the condition of the safety stitching on all sides. Look for any threads that are loose, worn, or cut.

4. Checking the condition of the rope clamp

- Check the condition of the rope clamp (marks, wear, cracks, deformation, corrosion...).

5. Checking the condition of the connectors

- For connector inspection, see the inspection form for your connector model at Petzl.com

6. Reinstalling the connectors

- Reinstall the connectors. Verify that the connector is correctly positioned in the rope clamp.
- Verify that the plastic protective sleeve correctly positions the connector

7. Function check

- Install your lanyard on an anchor at very low height.
- Check the smoothness of length adjustment for the lanyard.
 - Verify the locking effectiveness (no slippage when you are suspended on the lanyard).

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT
Product fit to remain in service
Product unfit to remain in service

Inspected by	
Company	
Date	Next inspection date