

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • PPE inspection should be conducted with the manufacturer's Instructions for Use.
 Download the instructions at [PETZL.COM](https://www.petzl.com).

EASYTOP / EASYTOP WALL

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

				N/A
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

				N/A
---	---	---	---	-----

2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

3. Inspecting the frame

- Check the condition of the frame (marks, cracks, wear, deformation, corrosion...).
- Check for wear caused by rope running through the device. Use the included inspection pin or a 4mm diameter bar.
- Check the condition of the anchor attachment hole (marks, cracks, wear, deformation, corrosion...).

4. Inspecting the primary gate

- Check the condition of the gate (marks, cracks, wear, deformation, corrosion...).
- Manually verify that the gate opens completely.
- Verify that the gate closes automatically and that the return spring works.
- Check the condition of the rivet (cracking, deformation, corrosion...).

5. Checking the auto-locking gate

- Check the condition of the gate (marks, cracks, wear, deformation, corrosion...).
- Manually verify that the gate opens completely.
- Verify that the gate closes automatically and that the return spring works.
- Check the condition of the rivet (cracking, deformation, corrosion...).

6. Checking the EASYTOP WALL anchor

- Check the condition of the anchor (marks, cracks, wear, deformation, corrosion...).
- Check the condition of the structure mounting holes (marks, cracks, wear, deformation, corrosion...).
- Check the condition of the EASYTOP installation bolt (marks, cracks, wear, deformation, corrosion...).

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date

Next inspection date