

- In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 - PPE inspection should be conducted with the manufacturer's Instructions for Use.
- Download the instructions at [PETZL.COM](https://www.petzl.com).

EJECT

User information

Surname

Address

Identifier

PPE information

Model


Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

				N/A
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

1. Known product history

Any PPE showing unexpected degradation should be quarantined, pending a detailed inspection.

The user should:

- Provide precise information on the usage conditions.

- Report any exceptional event regarding his/her PPE.

(Examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities).

				N/A
---	---	---	---	-----

2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new product to verify there are no modifications or missing parts.

3. Checking the condition of the strap

- Remove the strap from the pulley.
- Look for wear and damage due to use (cuts, fuzziness, signs of chemicals).
- Check the condition of all safety stitching on both sides. Look for any threads that are loose, worn, or cut.

4. Inspecting the pulley

- Check the condition of the pulley: marks, deformation, cracks, wear, corrosion, presence of the front and rear plastic covers.
 - Check the condition of the rivets: cracks, deformation, corrosion.
 - Check the condition of the gated attachment point: marks, deformation, cracks, wear, corrosion. Check especially: the latch hole, the latch itself, the anti-error tab and the area where the anti-error tab contacts the attachment point.
 - Check the condition of the opening lever: marks, deformation, cracks, wear, corrosion. Check that the return spring is working properly.
- Check the side plate for wear on the opening lever's guide-slot.
- Check the condition of the sheave (marks, deformation, cracks, corrosion, wear, absence of foreign bodies). Verify that the sheave turns freely in both directions.
 - Check the condition of the strap connection point. Verify that the O-ring is present on the screw. Check for wear or deformation of the side plates, in the screw holes and the threads. Check the condition of the screw: marks, deformation, cracks, wear, corrosion.

5. Pulley function check

- Check the movement of the anti-error tab: you must be able to push it in, and it must come back to position when released.
- Check the mobility of the gated attachment point. Verify that it closes properly and that the latch returns to position when the attachment point is closed.
- With the attachment point closed, check the upward mobility of the opening lever and the effectiveness of its return spring.
- Verify that the attachment point opens when the opening lever is pushed to the right. Verify that the lever returns to position when released.
- In case of dirt impeding the function of the lever, clean with soapy water and lubricate in the three places indicated in the diagram.

6. Inspecting the adjuster

- Check the condition of the adjuster: marks, deformation, cracks, wear, corrosion. Check the mobility of the cam and the effectiveness of its return spring.
- Reinstall the adjuster on the strap or on a replacement strap.
- Reinstall the strap on the pulley.

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT	
<input type="checkbox"/>	Product fit to remain in service
<input type="checkbox"/>	Product unfit to remain in service

Inspected by	
Company	
Date	Next inspection date