

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • PPE inspection should be conducted with the manufacturer's Instructions for Use.
 Download the instructions at [PETZL.COM](https://www.petzl.com).

REEVE

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

 Good condition (G)	 To monitor (TM)	 To repair (TR)	 Do not use, retire (R)	N/A Not applicable
---	--	---	---	-----------------------

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):






N/A

2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

3. Checking the general condition

- Check the general condition of the product (marks, deformation, cracks, wear, corrosion...).

4. Checking the attachment holes

- Check the condition of the attachment holes (marks, deformation, cracks, wear, corrosion...).

5. Checking the condition of the side plates

- Check the condition of the side plates (marks, deformation, cracks, wear, corrosion).
- Verify that the side plates rotate properly.
- Check the condition of the rivets (marks, deformation, cracks, wear, corrosion, absence of play...).

6. Checking the condition of the sheave(s)

- Check the condition of the sheaves (marks, deformation, cracks, corrosion, wear, absence of foreign bodies...).
- Verify that the sheave turns freely in both directions.

7. Checking the side plates' opening and locking systems

- Check the condition and function of the locking system (marks, deformation, dirt, effectiveness of the return spring(s)).

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date

Next inspection date