

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • PPE inspection should be conducted with the manufacturer's Instructions for Use.
 Download the instructions at [PETZL.COM](https://www.petzl.com).

PROGRESS CAPTURE PULLEY

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

 Good condition (G)	 To monitor (TM)	 To repair (TR)	 Do not use, retire (R)	N/A Not applicable
---	--	---	---	-----------------------

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):







2. Preliminary observations

Verify the presence and legibility of the serial number and the CE mark.
 Verify that the product lifetime has not been exceeded.
 Compare with a new device to verify there are no modifications or missing elements.

3. Checking the condition of the side plates

- Check the condition of the moving side plates (deformation, cracks, marks, wear, corrosion).
- Check the condition of the attachment hole (deformation, cracks, marks, wear, corrosion).
- If applicable, check the condition of the auxiliary attachment hole (deformation, cracks, marks, wear, corrosion).
- Check the condition of the rivets (deformation, cracks, marks, wear, corrosion, lack of play).
- Verify that the side plates rotate properly.

4. Checking the side plates' opening and locking systems

- Check the condition and function of the locking system (deformation, cracks, marks, wear, dirt, effectiveness of the return spring(s)).

5. Checking the cam

- Check the condition of the gate (deformation, cracks, marks, wear, corrosion, absence of foreign bodies). Check that all teeth are present and check their state of wear. The teeth must not be dirty. If necessary, clean them with a brush.
- Check the cam's rotation and the effectiveness of the return spring.
- Verify that the cam catch is working properly.

6. Checking the sheave

- Check the condition of the sheave (deformation, cracks, marks, wear, corrosion, absence of foreign bodies).
- Verify that the sheave turns freely in both directions.

7. Function check

- Install your pulley on an anchor and install a compatible rope around the sheave.
- With the cam deactivated, circulate the rope in both directions.
- With the cam activated, make sure the rope circulates in one direction and blocks in the other direction.

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by _____

Company _____

Date _____ Next inspection date _____