

- In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
  - PPE inspection should be conducted with the manufacturer's Instructions for Use.
- Download the instructions at [PETZL.COM](https://www.petzl.com).

## JAG RESCUE KIT

### User information

Surname

Address

Identifier

### PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

**Manufacturer:** Petzl, ZI Cidex 105A - 38920 Croles - France

				N/A
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

### 1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

					N/A
---	---	---	---	---	-----

### 2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

### 3. Inspection of all components

- Carry out the inspection of each component separately, using the dedicated procedures available at Petzl.com.
- The inspection may be done without dismantling the kit, by simply moving aside components that are hiding any parts to be inspected (e.g. rope in the I'D's closed auxiliary brake).
- If the kit has been disassembled during use or if a special inspection requires disassembling the kit's components, follow the assembly and repacking instructions beginning with section 4.

### 4. Reassembling the JAG RESCUE KIT

- Verify that the rope length is marked on a label on the rope. Verify that the length marked on the bag matches the length marked on the rope.
- Pack the rope in the bag, red sleeve first.
- Install a connector on the white sleeve end of the rope.
- I'D S < 2019 : Open the I'D S and put the handle in the belaying position. Install the rope in the I'D S with the white sleeve on the anti-error catch side. Close the side plate.
- I'D S > 2019 / I'D EVAC : Open the I'D S or I'D EVAC. Install the rope in the after-2019 I'D S or I'D EVAC with the white sleeve on the anti-error catch side. Close the side plate.
- Lock the moving side plate on the I'D S or I'D EVAC with the side plate locking screw.
- Install the RING OPEN on the JAG SYSTEM (JAG pulley side). Insert the pulley side plates and the edges of the cover, one after another, into the opening.
- In the event the rope is not installed in the closed auxiliary brake of the I'D EVAC, install the red sleeve (bag) end of the rope in the RING OPEN. Pass the red sleeve (bag) end of the rope through the RING OPEN and attach the I'D S or I'D EVAC to the RING OPEN. Close and lock the RING OPEN.
- Connect the JAG SYSTEM (JAG TRAXION progress-capture pulley side) to one end of the CONNEXION FIXE anchor strap.

### 5. Function check

Install your CONNEXION FIXE to an anchor at low height, with a light load on the white sleeve end of the rope.

- Verify that the system locks under load.
- Verify that it is possible to haul the load with the JAG SYSTEM.
- Verify that it is possible to lower the load with the I'D S or I'D EVAC.

### 6. Final packing

- Temporarily deactivate the JAG TRAXION cam and slide the cord through to set the JAG SYSTEM at maximum length. Reactivate the JAG TRAXION cam.
- Slide rope through to position the white sleeve as close as possible to the I'D S or I'D EVAC.
- Put the I'D S or I'D EVAC handle in LOCK position.
- Put everything in the bag, close, mark and seal according to your needs.

### Comments (detail here any defects found on the product and accomplished tasks)

VERDICT	
<input type="checkbox"/>	Product <b>fit</b> to remain in service
<input type="checkbox"/>	Product <b>unfit</b> to remain in service

Inspected by	
Company	
Date	Next inspection date