

- In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 - PPE inspection should be conducted with the manufacturer's Instructions for Use.
- Download the instructions at [PETZL.COM](https://www.petzl.com).

ASSISTED-BLOCKING BELAY DEVICES

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

				N/A
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

				N/A
--	--	--	--	-----

2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

3. Checking the moving side plate

- Check the condition of the moving side plate (e.g. deformation, cracks, marks, wear, corrosion, dirt). If you see a hole in the side plate, retire the product.
- If applicable, check the condition of the wear plate.
- Check the condition of the attachment hole (e.g. deformation, cracks, marks, wear, corrosion).
- Verify the presence and condition of the rivets (e.g. deformation, cracks, marks, wear, corrosion, lack of play).

4. Checking the condition of the frame

- Check the condition of the cam and its axle (e.g. deformation, cracks, marks, wear, corrosion, dirt). Check the mobility of the cam and the effectiveness of its spring.
- On the NEOX, check the condition of the faceted wheel (e.g. deformation, cracks, marks, wear, corrosion, dirt).
- Verify that the wheel rotates in both directions.
- Verify that the wheel moves upward, and check the effectiveness of the wheel's return spring.
- Check the condition of the friction plate (e.g. deformation, cracks, marks, wear, corrosion, dirt).
- Verify the absence of foreign objects (e.g. dirt) or lubricant on the rope path.
- Verify the presence and condition of the rivets (e.g. deformation, cracks, marks, wear, corrosion, lack of play).

5. Checking the condition of the handle

- Check the condition of the handle (e.g. deformation, cracks, marks, wear).
- Check that the handle return spring is working properly.

6. Checking the condition of the selector knob (GRIGRI + only)

- Check the condition of the selector knob (e.g. deformation, cracks, marks, wear, dirt).
- Check both settings of the selector knob for proper function. When the cam is rotated, it must offer more resistance in the lead climbing setting than in the top-rope setting.

7. Function check

- Carry out a function check with the device on the harness. Do this test with your smallest diameter rope.
 1. Pull on the climber side of the rope; the device should block the rope.
 2. Hang from a low height. Pull the handle while holding the brake side of the rope. The rope must slide through the device.
 3. Checking the anti-panic on the GRIGRI +. Hang from a low height. Pull the handle QUICKLY while holding the brake side of the rope. The rope must be blocked.

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date

Next inspection date