

• **In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person.** Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • **PPE inspection should be conducted with the manufacturer's Instructions for Use.**
 Download the instructions at PETZL.COM.

NAJA

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

 Good condition (G)	 To monitor (TM)	 To repair (TR)	 Do not use, retire (R)	N/A Not applicable
---	--	---	---	-----------------------

1. Known product history

Any PPE showing questionable degradation should be quarantined, pending a detailed inspection.
 The user should:
 - Provide precise information on the usage conditions.
 - Report any exceptional event regarding their PPE.
 (Examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities)

				N/A
---	---	---	---	-----

2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifespan has not been exceeded.
- Compare with a new product to verify there are no modifications or missing parts.

3. Checking the condition of the strap

- Remove the strap from the frame.
- Look for wear and damage due to use (cuts, fuzziness, signs of chemicals...).
- Check the condition of the safety stitching on both sides. Look for any threads that are loose, worn, or cut.

4. Inspecting the frame

- Check the condition of the frame: marks, deformation, cracks, wear, corrosion.
- Check the condition of the rivets: marks, deformation, cracks, wear, corrosion.
- Check the condition of the sheave (marks, deformation, cracks, corrosion, wear, absence of foreign objects). Verify that the sheave turns freely in both directions.
- Check the condition of the strap connection point. Verify that the O-ring is present on the screw. Check for wear or deformation of the frame, in the screw holes and the threads. Check the condition of the screw: marks, deformation, cracks, wear, corrosion.

5. Inspecting the retrieval sling

- Look for wear and damage due to use (cuts, fuzziness, signs of chemicals...).
- Check the condition of the safety stitching on both sides. Look for any threads that are loose, worn, or cut.
- Check the condition and function of the MINO retrieval accessory-carabiner and of its positioning bar.

6. Reinstall the strap on the frame

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT	
	Product fit to remain in service
	Product unfit to remain in service

Inspected by	
Company	
Date	Next inspection date