

• **In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person.** Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.
 • **PPE inspection should be conducted with the manufacturer's Instructions for Use.**
 Download the instructions at [PETZL.COM](https://www.petzl.com).

SWIVEL OPEN

User information

Surname

Address

Identifier

PPE information

Model

Serial number

Year of manufacture

Date of purchase

Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Croles - France

				N/A
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):







2. Preliminary observations

Verify the presence and legibility of the serial number and the CE mark.
 Verify that the product lifetime has not been exceeded.
 Compare with a new device to verify there are no modifications or missing elements.

3. Inspecting the frame

- Check the condition of the frame (e.g. deformation, cracks, marks, wear, corrosion).
- Move any connected device that conceals any part of the frame.
- Check for wear caused by rope movement, or by contact with anchors (depth of marks: retire your SWIVEL if it shows any wear greater than one mm deep. Check for the presence of any sharp edges, for example).

4. Checking the spacers and screws

- Check the condition of the spacers (e.g. deformation, cracks, marks, wear, corrosion).
- Check the tightening torque of the screws using a torque wrench (the tightening torque is specified in the Instructions for Use of the equipment).
- Remove the screws to check the equipment separately, only if the condition of the equipment requires it. In this case, see the mounting instructions indicated in the Instructions for Use.

5. Checking the axle and bearing

- Check the bearing for smoothness of rotation, in both directions.
 Make sure there is no excessive play between the two parts of the frame.
- Verify that the axle cover is present.
- Check the condition of the axle rivet (e.g. deformation, cracks, marks, wear, corrosion).

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date

Next inspection date