

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product.  
 • PPE inspection should be conducted with the manufacturer's Instructions for Use.  
 Download the instructions at [PETZL.COM](https://www.petzl.com).

# SPORT HARNESSSES

## User information

Surname

Address

Identifier

## PPE information

Model


Serial number

Year of manufacture

Date of purchase

Date of first use

**Manufacturer:** Petzl, ZI Cidex 105A - 38920 Crolles - France

				N/A
Good condition (G)	To monitor (TM)	To repair (TR)	Do not use, retire (R)	Not applicable

### 1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):

				N/A
--	--	--	--	-----

### 2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

### 3. Checking the condition of the straps

- Check for cuts, swelling, damage and wear due, for example, to use, to heat, and to contact with chemicals. Check the waistbelt straps, waistbelt bias tapes, and leg and shoulder straps if any. Be sure to check any areas hidden by buckles or protectors.
- Check the condition of all safety stitching on both sides. Look for any threads that are loose, worn, or cut. Safety stitching is identified by thread of a different color or surface appearance than that of the webbing.

### 4. Checking the tie-in points and belay loop

- Check the condition of the belay loop. Look for cuts, wear, swelling and damage due, for example, to use, to heat, to chemicals.
- Check the condition of the protective webbing on the tie-in points. Look for cuts, wear, swelling and damage due, for example, to use, to heat, to chemicals.

If the protective webbing on the tie-in points shows signs of wear (holes, cut threads, frayed webbing), retire your harness. Certain harnesses (e.g. SIMBA, LUNA, SELENA, ADJAMA, SAMA sold up until 2018) have a red wear indicator on the lower tie-in point. Retire your harness if this indicator is visible.

- Verify that the screws on the gated attachment point are present and properly tightened.
- Verify the absence of deformation, cracks, marks, wear, corrosion.

### 5. Checking the condition of the adjustment buckles

- See your harness Instructions for Use.
- Check the condition of the adjustment buckles (absence of deformation, cracks, marks, wear, corrosion...).
- Check that the straps are correctly threaded, with no twists.
- Verify that the buckles operate properly.

### 6. Special case for FLY harness

- Verify the knots are present and check the condition of the cord.
- Look for cuts, wear, swelling and damage due, for example, to use, to heat, to chemicals.
- Verify that the toggle and the waistbelt elastic band are working properly.

### 7. Checking the comfort parts

- Check the condition of the waist and leg foams (cuts, wear, tears...).
- Check the condition of the elastic keepers and leg loop elastic bands (cuts, wear, tears...).
- Check the condition of the equipment loops (cuts, wear, tears...).

### Comments (detail here any defects found on the product and accomplished tasks)

#### VERDICT

Product **fit** to remain in service

Product **unfit** to remain in service

Inspected by

Company

Date

Next inspection date